

ADC EWH 350G OPL WASHER



Features and Benefits:

- Soft Mount 350G
- Variable Frequency Drive (VFD)
- Easy to program / Easy to control
- Heavy duty, ergonomic door and handle
- Stainless steel cabinet and basket standard
- 7 External chemical injection ports
- OPTIONAL MP control - 99 programs, 16 fixed washing programs



EcoWash 350G Soft Mount

High Spin

EWH-25

EWH-30

EWH-40



Soft Mount

EcoWash high spin washer/extractors (350G) feature a heavy-duty cast aluminum bearing housing support and our automatic imbalance detection system. Together these provide maximum stability and gentler movement, prolonging the unit's life.

Durable Door Safety Lock and Handle

The durable ergonomic design of the door handle combined with our Easy Lock™ door lock provides maximum convenience and safety.

10 Year Limited Manufacturer's Limited Warranty

ADC's EcoWash machines carry a 10 year manufacturer's warranty assuring owners that you've invested in superior performance, quality, durability and reliability.

* Refer to specific warranty for details

M Control (Standard)

- Basic consumption microprocessor
 - 16 standard washing programs with option to select as standard any of them
 - Selectable water levels
 - Option to modify times and temperatures in each phase and even to remove any phase

MP Control (Optional)

- MP Controller optimizes energy consumption efficiently by measuring the load as it is introduced to the washer. The washer automatically adapts and fills both water and chemicals to the proper levels.
- 99 programs, 16 fixed with an additional 83 available
- Adjustable water levels

	EW-25 (350 G-Force)	EW-30 (350 G-Force)	EW-40 (350 G-Force)
DRUM			
Load Capacity (lb/kg)	25 / 10	30 / 13	40 / 18
Drum Volume (cu. ft./liter)	3.53 / 100	4.6 / 130	6.35 / 180
Drum Diameter (in/mm)	21 / 533	24.41 / 620	27.56 / 700
Drum Depth (in/mm)	16.75 / 425	16.94 / 430	18.50 / 470
DIMENSIONS			
Width (in/mm)	27.25 / 692	31.02 / 788	34.8 / 884
Depth (in/mm)	31.125 / 790	31.50 / 800	33.25 / 844
Height (in/mm)	45.47 / 1155	58.18 / 1308	52.28 / 1404
Weight (lb/Kg)	507 / 229.97	551 / 250	794 / 360.16
DIMENSIONS WITH PACKAGING			
Crated Width (in/mm)	29.125 / 739	32.50 / 826	36.25 / 921
Crated Depth (in/mm)	39.125 / 994	39.50 / 1003	41 / 1041
Crated Height (in/mm)	53.75 / 1365	59.50 / 1511	65.25 / 1657
Crated Weight (lb/Kg)	522 / 236.78	591 / 268.07	844 / 382.83
DOOR			
Height to Bottom of Door (in/mm)	16.75 / 425	17.75 / 451	19.75 / 502
Door Opening Diameter (in/mm)	11.50 / 292	14.75 / 375	14.75 / 375
POWER			
Voltage/Phase	208-240 / 1, 3ø	208-240 / 1, 3ø	208-240 / 1, 3ø
Full load current / Breaker (amps) - 1ø	5.26 / 15	6.35 / 15	11.56 / 15
Full load current / Breaker (amps) - 3ø	3.88 / 15	4.51 / 15	7.53 / 15
CONNECTIONS			
Water Inlet (in/mm)	.75 / 19.05	.75 / 19.05	.75 / 19.05
Steam Inlet (in/mm)	.50 / 12.7	.50 / 12.7	.50 / 12.7
Drain (in/mm)	3 / 76.2	3 / 76.2	3 / 76.2
CYLINDER SPEED			
Washing speed (r.p.m.)	50	50	47
Spinning speed (r.p.m.)	1000	1000	950
G-Force	350	350	350
FLOOR LOADING			
Static Floor Load	507 lb / 2,30 kN	551 lb / 2,50 kN	793 lb / 3,60 kN
Dynamic Floor Load	166 lb / 0,75 kN	231 lb / 1,05 kN	308 lb / 1,40 kN
Maximum Vertical Load	636 lb / 3,05 kN	782 lb / 3,55 kN	1102 lb / 5 kN
Dynamic Load Frequency (Hz)	16,7	16,7	16
G Factor	350	350	350
OPTIONAL HEAT SOURCES			
Steam Inlet (in/cm)	.50 / 1.27	.50 / 1.27	.50 / 1.27
Electric	6 kW	9 kW	12 kW

