



TP SERIES 100-G Commercial Washer-Extractor

- FWS-25 TP
- FWS-30 TP
- FWS-40 TP
- FWS-60 TP
- FWS-80 TP
- FWS-135 TP

This new generation of washers combines the latest technology with the best quality in components and materials. They are equipped with the most advanced technology in water and energy saving systems, as well as the WET CLEANING feature. Its user friendly and intuitive programming makes them suitable for all types of laundries, dry- cleaners, self-service, commercial or industrial laundries, hospitals and nursery homes.

The latest features and technology at you service:

- STAINLESS STEEL DESIGN
- EFFICIENT MIX
- BALANCE CONTROL
- TOUCH PLUS CONTROL
- MULTI-CHOICE INLET
- WET CLEANING
- MAINT. CARE
- OPTIMIZED DRUM
- OPTIMAL CONSUMP.



Powerful Flexible "Control your budget"

The laundry operator can easily program, retrieve data and create wash cycle reports through USB and laptop PC. A simple access to data bank and easy programming the TP control helps save time and ensures the correct laundry process. Trouble shooting friendly.



Built to Last Ergonomic Door System

Loading and unloading are fast and easy through the oversized ergonomic door system that opens 180 degrees. No more wasted time due to door lock error codes. Fagor maintained your laundry business running at a full productivity.



User friendly chemical dispensing

The four compartment dispenser ensures a consistent cleaning process in every wash, which it eliminate the possibility of overuse, that can result in damage fabric due to operator error.



Quality Construction and Durability A-Frame

Rugged A-Frame Design offers excellent strength and stability for better performance. Washer feature inner, outer cylinder, front and side panels of durable stainless steel. Oversize bearings and housing assure superior quality & longevity over the life time of the washer.

Low Speed Industrial-Commercial Strength Washer-Extractor, a Fagor Commercial product line, engineered to deliver energy efficiency, performance and to manage unmatched wash quality performance. The robust design will last for years and the performance has proven to be extremely reliable in the industry.

What makes Fagor a true commercial product and energy efficient?

MODELS	FWS-25TP	FWS-30TP	FWS-40TP	FWS-60TP	FWS-80TP	FWS-135 TP
LOAD CAPACITY (lb/kg)	25 / 10	30 / 13	40 / 18	60 / 25	80 / 35	135 / 60
CYLINDER VOLUME (cu. ft. / liter)	3.5 / 100	4.6 / 130	6.4 / 181	8.7 / 247	12.3 / 350	23.23 / 590
CYLINDER DIAMETER (in / mm)	24 3/8 / 620	24 3/8 / 620	27 / 700	30 3/8 / 770	33 7/8 / 860	41.26 / 1048
CYLINDER DEPTH (in / mm)	13 / 330	16 7/8 / 430	18 / 470	20 7/8 / 530	23 7/8 / 602	26.93 / 684
WIDTH (in / mm)	28 / 719	28 1/4 / 719	31 / 788	34 / 884	38 / 979	48.23 / 1225
DEPTH (cabinet) (in / mm)	25 3/8 / 645	31 1/8 / 791	31 / 800	38 / 965	41 5/8 / 1057	47.64 / 1210
DEPTH (overall) (in / mm)	29 1/8 / 749	34 5/8 / 879	35 1/8 / 892	40 1/2 / 1029	44 7/8 / 1140	50.39 / 1280
HEIGHT (in / mm)	45 5/8 / 1157	45 5/8 / 1157	51 / 1307	51 / 1307	55 / 1411	64.57 / 1640
WEIGHT (lb/kg)	450 / 204	518 / 235	591 / 268	794 / 360	1032 / 468	930 / 2050
SHIPPING DIMENSIONS APPROX. - in (in / mm) with packaging						
CRATED WIDTH (in / mm)	31 / 800	32 / 813	34 / 884	36 / 927	42 / 1073	53.54 / 1360
CRATED DEPTH (in / mm)	33 / 851	39 / 997	41 / 1048	45 / 1149	49 / 1257	57.48 / 1460
CRATED HEIGHT (in / mm)	54 / 1391	54 / 1391	60 / 1543	60 / 1530	65 / 1657	74.06 / 1880
CRATED WEIGHT (lb / kg)	506 / 230	568 / 258	647 / 294	867 / 394	1122 / 510	2314.85/1050
DOOR						
HEIGHT TO BOTTOM OF DOOR	12 / 310	12 / 310	15 5/8 / 395	16 / 419	14 5/8 / 373	21.22 / 539
DOOR OPENING DIAMETER (in / mm)	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	22 / 560	22.05 / 560
POWER						
VOLTAGE / Phase (50 hz or 60 hz)	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH
Full Load Current / Breaker (amps) - 1PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 20	13.7 / 20	N / A
Power of Motor (Kw)	0.75	1.5	2.2	2.2	3	5.5
Heating Power (Electric Heating Models) (Kw)	6	9	12	18	21	3.6
Heating Power (Steam and Hot Water Heating) (Kw)	6.25	9.5	12.75	19	3	5.5
CONNECTIONS						
Water Inlet (GHT/BSP)	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4
Steam Inlet (GHT/BSP)	1/2	1/2	1/2	3/4	3/4	3/4
Drain (in / mm)	3 / 76	3 / 76	3 / 76	3 / 76	3 / 76	3 / 76
CYLINDER SPEED						
Washing Speed (rpm)	53	53	50	48	45	45
Spinning Speed (rpm)	538	538	507	483	458	458
G-Force	100	100	100	100	100	100
WATER						
Average Usage (gallons)*	18.3	29	36.8	42.6	59.9	151.8

Standard Features:

- Heavy duty frame
- Stainless steel panels
- Hinged control panel
- Flexible water level setting
- 5 compartment supply dispenser
- 8 external liquid supply dispenser
- Water reuse capable
- Enclosed heavy duty drive motor
- Large door opening
- Third inlet valve
- Wet cleaning capable
- Traceability – storage of data.

Optional Features:

- Double drain kit allow the recovery of the water, with important savings.
- Drain-pump kit (25lbs and 30lbs).
- Double heating electric-steam kit.
- 6 extra signals for automatic liquid dosing.
- Industrial voltage: 440 ÷ 480 III without neutral - 50 / 60 Hz.

To learn more, or to find a distributor in your area, visit www.fagorcommercial.com



* Agency approvals may vary depending on configuration. Consult factory or dealer for details. For the most accurate information, please consult machine installation manual for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.