



TP SERIES 200-G

Commercial Washer-Extractor

FWR-25 TP
FWR-30 TP
FWR-40 TP
FWR-60 TP



This new generation of washers combines the latest technology with the best quality in components and materials. They are equipped with the most advanced technology in water and energy saving systems, as well as the WET CLEANING feature. Its user friendly and intuitive programming makes them suitable for all types of laundries, dry- cleaners, self-service, commercial or industrial laundries, hospitals and nursery homes.

The latest features and technology at you service:

- STAINLESS STEEL DESIGN
- EFFICIENT MIX
- BALANCE CONTROL
- TOUCH PLUS CONTROL
- MULTI-CHOICE INLET
- WET CLEANING
- MAINT. CARE
- OPTIMIZED DRUM
- OPTIMAL CONSUMP.



Powerful Flexible "Control your budget"

The laundry operator can easily program, retrieve data and create wash cycle reports through USB and laptop PC. A simple access to data bank and easy programming the TP control helps save time and ensures the correct laundry process. Trouble shooting friendly.



Built to Last Ergonomic Door System

Loading and unloading are fast and easy through the oversized ergonomic door system that opens 180 degrees. No more wasted time due to door lock error codes. Fagor maintained your laundry business running at a full productivity.



User friendly chemical dispensing

The four compartment dispenser ensures a consistent cleaning process in every wash, which it eliminate the possibility of overuse, that can result in damage fabric due to operator error.



Quality Construction and Durability A-Frame

Rugged A-Frame Design offers excellent strength and stability for better performance. Washer feature inner, outer cylinder, front and side panels of durable stainless steel. Oversize bearings and housing assure superior quality & longevity over the life time of the washer.

Mid Speed Industrial-Commercial Strength Washer-Extractor, a Fagor Commercial product line, engineered to deliver energy efficiency, performance and to manage unmatched wash quality performance. The robust design will last for years and the performance has proven to be extremely reliable in the industry.

What makes Fagor a true commercial product and energy efficient?

MODELS	FWR-25TP	FWR-30TP	FWR-40TP	FWR-60TP
LOAD CAPACITY (lb/kg)	25 / 11	30 / 13	40 / 18	60 / 25
CYLINDER VOLUME (cu. ft. / liter)	3.5 / 100	4.6 / 130	6.4 / 181	8.7 / 247
CYLINDER DIAMETER (in / mm)	24 3/8 / 620	24 3/8 / 620	27 / 700	30 3/8 / 770
CYLINDER DEPTH (in / mm)	13 / 330	16 7/8 / 430	18 / 470	20 7/8 / 530
WIDTH (in / mm)	28 / 719	28 / 719	31 / 788	34 / 884
DEPTH (cabinet) (in / mm)	25 3/8 / 645	31 1/8 / 791	31 / 800	38 / 965
DEPTH (overall) (in / mm)	28 5/8 / 727	34 1/2 / 876	35 1/8 / 892	40 1/2 / 1029
HEIGHT (in / mm)	45 5/8 / 1157	45 5/8 / 1157	51 / 1307	51 7/8 / 1319
WEIGHT (lb/kg)	467 / 212	531 / 241	622 / 282	891 / 404
SHIPPING DIMENSIONS APPROX. - in (in / mm) with packaging				
CRATED WIDTH (in / mm)	31 / 800	31 / 800	34 / 883	37 / 959
CRATED DEPTH (in / mm)	33 / 851	40 / 1029	40 / 1029	45 / 1192
CRATED HEIGHT (in / mm)	54 / 1391	54 / 1391	60 / 1543	61 / 1562
CRATED WEIGHT (lb / kg)	517 / 235	581 / 264	678 / 308	964 / 438
DOOR				
HEIGHT TO BOTTOM OF DOOR	12 / 310	12 / 310	15 5/8 / 395	17 / 433
DOOR OPENING DIAMETER (in / mm)	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373
POWER				
VOLTAGE / Phase (50 hz or 60 hz)	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH
Full Load Current / Breaker (amps) - 1PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 20
Power of Motor (Kw)	0.75	1.5	2.2	3
Heating Power (Electric Heating Models) (Kw)	6	9	12	18
Heating Power (Steam and Hot Water Heating) (Kw)	6.25	9.5	12.75	19
CONNECTIONS				
Water Inlet (GHT/BSP)	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4
Steam Inlet (GHT/BSP)	1/2	1/2	1/2	3/4
Drain (in / mm)	3 / 76	3 / 76	3 / 76	3 / 76
CYLINDER SPEED				
Washing Speed (rpm)	50	50	47	45
Spinning Speed (rpm)	760	760	760	714
G-Force	200	200	200	200
WATER				
Average Usage (gallons)*	18.3	29	36.8	42.6

* Agency approvals may vary depending on configuration. Consult factory or dealer for details. For the most accurate information, please consult machine installation manual for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.

Standard Features:

- Heavy duty frame
- Stainless steel panels
- Hinged control panel
- Flexible water level setting
- 5 compartment supply dispenser
- 8 external liquid supply dispenser
- Water reuse capable
- Enclosed heavy duty drive motor
- Large door opening
- Third inlet valve
- Wet cleaning capable
- Traceability – storage of data.

Optional Features:

- Double drain kit allow the recovery of the water, with important savings.
- Drain-pump kit (25lbs and 30lbs).
- Double heating electric-steam kit.
- 6 extra signals for automatic liquid dosing.
- Industrial voltage: 440 ÷ 480 III without neutral - 50 / 60 Hz.

To learn more, or to find a distributor in your area, visit www.fagorcommercial.com

